

### PERMANENT MAGNETIC VARIABLE FREQUENCY PUMP

**Product Overview:**

- Over flow pas are 304 stainless steel, in line with drinking water sanitation standards.
- Shaft seal for the mechanical seal, different media choose the friction accordingly.
- F class insulation, IP54 protection grade.
- Supporting LCD display human-machine interact, simple operation.
- Equipped with industrial grade pressure sensors.
- Multiple pumps can be network online.

**Feature:**

- Constant pressure
- Efficient
- Energy saving
- Comfortable
- Low Noise
- Wet End 100% Anticorrosive

**Pump Material:**

- Stainless steel pump body, stainless steel impeller, 304 welding shaft, silicon carbide to graphite mechanical seal, Sensata pressure sensor, stainless steel five-way, stainless steel oil pressure gauge, IP54

**Scope Application:**

- It is suitable for domestic water supply of various types of water works, pressure station, hotels, residential areas and others high-rise buildings.



Model	SFG404
Power (w)	1100
Voltage (V)	220V, 50Hz
Max. Speed (rpm)	3450
Max. Flow (m <sup>3</sup> /h)	7.8
Inlet Size	1.5 inch
Inlet Size	1.0 inch
Max. Pressure Rate	4.8 Bar @ 40L/min
Min. Pressure Rate	2.4 Bar @ 110L/min
Max Head (m)	54
Rate Head (m)	42
Dimension (cm)	WxDxH 37 x 40 x 45
Weight (kg)	13